USN

Sixth Semester B.E. Degree Examination, June/July 2017

Transportation Engineering – II

Time: 3 hrs. Max. Marks:100

Note: 1. Answer FIVE full questions, selecting at least TWO questions from each part.
2. Missing data, if any, may be suitably assumed.

PART - A

- 1 a. Mention the different gauges that are used in Indian railways. Discuss the factors affecting adoption of a particular gauge. (06 Marks)
 - b. With neat sketches, explain coning of wheels and tilting of rails. (06 Marks)
 - c. What is meant by wear of rails? How do you classify the wear? Discuss the various causes of wear. (08 Marks)
- 2 a. List the different fixtures used in railway track and give the dimensional sketch of fish plate.

 (06 Marks)
 - b. Determine the quantity of materials required to construct a 800 m long BG railway track, assuming a sleeper density of (n + 5). (06 Marks)
 - c. Calculate the maximum permissible train load that a B.G. locomotive can haul with 3 pairs of driving wheels with axle load of 22 kN each on a straight level track at a speed of 80 kmph. Calculate the reduction in speed, if the train has to run on a rising gradient of 1 in 200. What would be the further reduction in speed if the train has to negotiate a 4° curve on the rising gradient? Assume coefficient of friction as 0.2. (08 Marks)
- 3 a. Define: i) Super elevation
- ii) Negative cant
- iii) Cant deficiency
- iv) Grade compensation on curves
- (06 Marks)
- An 8° curve branches off from 4° main curve in B.G. layout. If the speed on branch line is 28 kmph, find the speed on main line. Cant deficiency is 7.61 cm. (06 Marks)
- c. Calculate the maximum permissible speed on a curve of highspeed B.G. track having the following particulars:

Degree of curve = 1°

Amount of super elevation = 8 cm

Length of transition curve = 130 m

Max. speed of the section likely to be sanctioned = 153 kmph.

(08 Marks)

- a. Calculate the elements of a BG turnout, if feel divergence is 11.43 cm. Number of crossing is 16 and angle of switch is 1°8′0″. Straight arm distance = 0.9 m. (06 Marks)
 - b. With a neat sketch show the details of acute angle crossing. Indicate: i) actual, ii) theoretical rose of crossing. (06 Marks)
 - c. What is signaling? What are the objectives of signaling? List the types of signals. (08 Marks)

PART - B

5 a. Write a note on aircraft characteristics.

- (08 Marks)
- b. Define wind rose diagram. With a neat sketch, explain the method of locating the best orientation of runway. (06 Marks)
- c. Write a note on airport classification.

6 a. A taxiway is to be designed for operating a Boeing aircraft, which has the following characteristics. Determine the turning radius of the taxiway.

Wheel base W = 17.70 m

Tread of main gear = 6.62 m

Width of taxiway, T = 22.5 m

Turn-off speed = 40 kmph

Coefficient of friction = 0.3

(06 Marks)

b. Explain the various types of airport markings.

- (06 Marks)
- c. An airport is planned at an elevation of 380 m above MSL. The monthly mean of maximum and average daily temperatures for the hottest month at the site are 40°C and 28°C respectively. The effective gradient is 0.18 percent. Determine the length of runway required at the proposed site if the basic runway length is 1900 m. (08 Marks)
- 7 a. Write short notes on:
 - i) Tunnel lining
 - ii) Tunnel drainage
 - b. Explain various shapes of tunnel with neat sketches.

(06 Marks) (06 Marks)

(08 Marks)

- c. With a neat sketch, explain the needle beam method of tunneling in soft soils.
- **8** a. Explain the functions of :
 - i) Wharfs and quays
 - ii) Wet and dry docks

(08 Marks)

b. Draw a neat sketch of artificial harbor, explain the various components.

(06 Marks)

c. Define breakwater. Explain any one type of breakwater.

(06 Marks)

* * * * *